



LAMP TYPE	SOCKET	A (mm)	B (mm)	H (mm)	K.G.
2x14 / 2x24 W T5	G5	150	614	64	3,4
2x21 / 2x39 W T5	G5	150	914	64	3,8
2x28 / 2x54 W T5	G5	150	1215	64	4,7
2x35 / 2x80 W T5	G5	150	1514	64	5,3
2x36 W T8	G13	150	1264	64	4,8

BOX / KOLİ
(mm)



LAMP TYPE	SOCKET	A (mm)	B (mm)	H (mm)	K.G.
2x24 W CT	2G11	150	905	64	3,2
2x36 W CT	2G11	150	1070	64	3,5
2x40 W CT	2G11	150	1200	64	4,6
2x55 W CT	2G11	150	1200	64	5,2

BOX / KOLİ
(mm)



GEAS 2100

- BODY** : Aluminium Body
- GLASS/DIFFUSER** : UV - Stabilized Acrylic Diffuser With High Light-Transmission Permeability
- REFLECTOR** : Bright or Matt Aluminium Inner Reflector
- ELECTRICAL COMP** : Magnetic / Electronic / Dimmable Ballast, Emergency Kit Additionally Applicable
- PROTECTION CLASS**: IP 40
- OTHER FEATURES** : Easy Installation Suspension System.
Direct Lighting or Direct-Indirect Lighting Versions Available
- USAGE AREAS** : Offices, Hallways, Stairs, Stores, Hotels, Conference Halls, Shopping Centers, Structure Entrances, Classrooms, Custom and Decorative Locations

- GÖVDE** : Alüminyum Gövde
- CAM/DİFÜZÖR** : UV Stabilizeli Yüksek Geçirgenlikli Akrilik Difüzör
- REFLEKTÖR** : Parlak veya Mat Alüminyum İç Reflektörler
- ELEKTRİKSEL KOMP**: Manyetik / Elektronik / Dim Edilebilir Balast ve Ek Uygulanabilir Emergency Kit (Acil Kit)
- KORUMA SINIFI** : IP 40
- DİĞER ÖZELLİKLER** : Kolay Montaj Askı Sistemi.
Direkt Aydınlatma veya Direkt-Endirekt Aydınlatma Versiyon Seçeneği
- KULLANIM ALANLARI** : Ofisler, Koridorlar, Merdivenler, Mağazalar, Oteller, Konferans Salonları, Alışveriş Merkezleri, Bina Girişleri, Derslikler, Özel ve Dekoratif Mekanlar

GEAS 2200

