

LAMP TYPE	SOCKET	A (mm)	B (mm)	H (mm)	K.G.
1x20 W M.H. CDM-R 111	Gx8.5	195	195	205	2,2
1x35 W M.H. CDM-R / R 111	E27/Gx8.5	195	195	205	2,3
1x70 W M.H. CDM-R / R 111	E27/Gx8.5	195	195	205	2,2
1x35 W M.H. CDM-T	G12	195	195	205	2,4
1x70 W M.H. CDM-T	G12	195	195	205	2,5



Electrical components placed inside protection cover mounted on luminaire itself. An independent external ballast module with 1 m. Length cable supplied optionally on request.


Elektriksel komponentler koruyucu kapak altında yer almaktadır, bağımsız dışış balast modülü opsiyonel ekipman olarak 1 m. lik kablo ile talep dahilinde üretilmektedir.



Opposite directional -25, +25 degrees movable on vertical and horizontal planes. Ters yönde -25, +25 derece yatay ve dikey ekseninde.




LAMP TYPE	SOCKET	A (mm)	B (mm)	H (mm)	K.G.
2x20 W M.H. CDM-R 111	Gx8.5	195	345	205	2,9
2x35 W M.H. CDM-R / R 111	E27/Gx8.5	195	345	205	3,1
2x70 W M.H. CDM-R / R 111	E27/Gx8.5	195	345	205	3,3
2x35 W M.H. CDM-T	G12	195	345	205	3,1
2x70 W M.H. CDM-T	G12	195	345	205	3,2



Electrical components placed inside protection cover mounted on luminaire itself. An independent external ballast module with 1 m. Length cable supplied optionally on request.

Elektriksel komponentler koruyucu kapak altında yer almaktadır, bağımsız dışış balast modülü opsiyonel ekipman olarak 1 m. lik kablo ile talep dahilinde üretilmektedir.



GMZ 301

- BODY** : DKP Metal & Electrostatic Painted
- GLASS/DIFFUSER** : Circular Sanblasted Glass
- REFLECTOR** : Special Coated Aluminium Reflector For Maximum Reflection and Efficiency
- ELECTRICAL COMP** : Magnetic / Electronic Option
- PROTECTION CLASS**: IP 20
- OTHER FEATURES** : Double Axis Angle Adjustable Lamp and Reflector Part. Aluminium Die-Cast Reflector Ring
- USAGE AREAS** : Offices, Shops, Hotels, Conference Halls, Showcases and Similar Special Purposed Precision Optical Light Distribution Demanded Interior Applications Which Paid Attention Also Decoration

- GÖVDE** : DKP Sac & Elektrostatik Boyalı
- CAM/DİFÜZÖR** : Dairesel Kuşlamalı Cam
- REFLEKTÖR** : Maksimum Yansıma ve Verim için Özel Kaplamalı Alüminyum Reflektör
- ELEKTRİKSEL KOMP**: Manyetik / Elektronik Seçeneği.
- KORUMA SINIFI** : IP 20
- DİĞER ÖZELLİKLER** : Çift Eksen Açılı Ayarlanabilir Ampul ve Reflektör Kısmı Alüminyum Enjeksiyon Reflektör Çerçevesi
- KULLANIM ALANLARI** : Ofisler, Mağazalar, Oteller, Konferans Salonları, Vitrinler Gibi Özel Hassasiyette Optik Işık Dağılımı İstenen ve Dekoratif Görünümü İhtiyaç Gösterilen İç Mekan Aydınlatma Uygulamaları

GMZ 302

