



GSSD 175



LAMP TYPE	SOCKET	Ø A (mm)	H (mm)	K.G.
1x13 W CT	G24d	205	210	1,45
1x18 W CT	G24d	205	210	1,54
1x26 W CT	G24d	205	210	1,65
1x27 W ECO (Max)	E27	205	210	1,50

BOX / KOLİ
(mm)




GSSD 400



LAMP TYPE	SOCKET	Ø A (mm)	H (mm)	K.G.
1x13 W CT	G24d	145	190	1,1
1x18 W CT	G24d	145	190	1,2
1x26 W CT	G24d	145	190	1,6
1x27 W ECO (Max)	E27	145	190	1,5

BOX / KOLİ
(mm)



GSSD

- BODY** : Aluminium Chrome-Plated or ABS Chrome Plated Frame
DKP Metal & Electrostatic Painted (GSSD 400)
- GLASS/DIFFUSER** : Circular Sanblasted Glass (GSSD 400)
- REFLECTOR** : Special Coated Aluminium Reflector For Maximum Reflection and Efficiency
- ELECTRICAL COMP** : Magnetic / Electronic / Dimmable Ballast, Emergency Kit Additionally Applicable
- PROTECTION CLASS**: IP 20
IP 40 (GSSD 400)
- OTHER FEATURES** : Lamp Suitable for Vertical Use
Easy Montage With Integrated Ballast Box and Coupling Connectors.
Easy Removable Frame for Painting of Ceilings Without Removal
- USAGE AREAS** : Interiors, Plaster Ceiling Applications, Conference Halls, Shopping Malls, Hallways, Offices, Shopping Windows

- GÖVDE** : Alüminyum Kromaj Kaplama veya ABS Kromaj Kaplama Çerçeve
DKP Sac & Elektrostatik Boyalı (GSSD 400)
- CAM/DİFÜZÖR** : Dairesel Kumlamalı Cam (GSSD 400)
- REFLEKTÖR** : Maksimum Yansıma ve Verim için Özel Kaplamalı Alüminyum Reflektör
- ELEKTRİKSEL KOMP**: Manyetik / Elektronik / Dim Edilebilir Balast ve Ek Uygulanabilir Emergency Kit (Acil Kit)
- KORUMA SINIFI** : IP 20
IP 40 (GSSD 400)
- DiĞER ÖZELLİKLER** : Dikey Ampul Kullanımına Uygun Gövdeye Entegre Balast Kutusu ve Geçme Konnektörler ile Kolay Montaj,
Sökme Gerekirmeden Tavan Boyama İçin Kolay Çıkarılabilir Çerçeve
- KULLANIM ALANLARI** : İç mekanlar, Alçı Tavan Uygulamaları, Konferans Salonları, Alışveriş Merkezleri, Koridorlar, Ofisler, Vitrinler

