



A compact luminaire with easy serviceability and low total cost ownership (TCO).
Düşük sahip olma (TCO) maliyetine, yüksek servisebiliteye sahip bir armatür.



Easy access lamp compartment
Kolay erişilebilir ampul haznesi



Aluminium extrusion pole entrance
Alüminyum ekstrüzyon kuyruk

LAMP TYPE	SOCKET	A (mm)	B (mm)	H (mm)	K.G.
1x50 W SOD.	E40	260	470	196	3,6
1x70 W SOD. // M.H.	E27	260	470	196	3,7
1x125 W MER.	E27	260	470	196	3,4
1x100 / 1x150W SOD.	E40	260	470	196	4,4
1x100 / 1x150W M.H.	E40	260	470	196	4,3
2x26 CT. // 2x27 ECO. G24d / E27	G24d / E27	260	470	196	2,4 / 3,2



AMS-65E

- BODY** : Aluminium, Bright-Anodized Coating
- GLASS/DIFFUSER** : UV - Stabilized Polycarbonate Monoblock Glass
- REFLECTOR** : On Housing Total Reflection With Bright Anodization.
- ELECTRICAL COMP** : On Module, High Efficient Ballast, Ignitor, Capacitor (Optional)
- PROTECTION CLASS**: IP65
- OTHER FEATURES** : High Temperature and Impact Resistancy
Optimum Light Distribution
Isolation with PU Gasketing
Aluminium Extrusion Latches
Maximum Resistancy to Dust, Water and Moisture
Aluminium Extrusion Pole Entrance
Appropriate to 42mm and 60mm Poles
Galvanized Ballast and Electrical Components Connection Kit
- USAGE AREAS** : Roads, Highways, Surrounding Area Lightings, Walkways, Streets and Various Outdoor Lighting Applications

- GÖVDE** : Parlak Eloksoal Kaplamalı Alüminyum
- CAM / DİFÜZÖR** : UV Stabilizeli Polikarbonat Monoblok Cam
- REFLEKTÖR** : Parlak Eloksoal Kaplama İle Gövdeye Tümlüşik Yansıma
- ELEKTRİKSEL KOMP**: Kit Halinde, Yüksek Verimli Balast, İgnitör, Kondansatör (Opsiyonel)
- KORUMA SINIFI** : IP65
- DIĞER ÖZELLİKLER** : Optimum Işık Dağılımı.
PU Dökme Conta İzolasyonu
Alüminyum Ekstrüzyon Mandallar
Toz, Nem ve Suya Karşı Maksimum Dayanıklılık
Çap 42 ve 60 mm Boruya Uygun Alüminyum Ekstrüzyon Kuyruk
Galvaniz Balast ve Elektriksel Elemanlar Bağlantı Kiti
- KULLANIM ALANLARI** : Caddeler, Otoyollar, Çevre Aydınlatmaları, Gezinti Yolları, Sokaklar, Her Tür Dış Mekan Aydınlatma Uygulamaları

