



## AMS 65-LD

- BODY** : Electrostatic Painted Aluminum
- GLASS/DIFFUSER** : UV - Stabilized Polycarbonate Monoblock Glass
- REFLECTOR** :
- ELECTRICAL COMP** : Switch Mode, Constant Current LED Power Supply
- PROTECTION CLASS**: IP65
- OTHER FEATURES** : High Temperature and Impact Resistancy  
Optimum Light Distribution  
Isolation with PU Gasketing  
Aluminium Extrusion Latches  
Maximum Resistancy to Dust, Water and Moisture  
Aluminium Extrusion Pole Entrance  
Appropriate to 42mm and 60mm Poles
- USAGE AREAS** : Roads, Highways, Surrounding Area Lightings, Walkways, Streets and Various Outdoor Lighting Applications
- GÖVDE** : Elektrostatik Boyalı Alüminyum
- CAM / DİFÜZÖR** : UV Stabilizeli Polikarbonat Monoblok Cam
- REFLEKTÖR** :
- ELEKTRİKSEL KOMP**: Switch Mode, Sabit Akım LED Güç Kaynağı
- KORUMA SINIFI** : IP65
- DİĞER ÖZELLİKLER** : Optimum Işık Dağılımı.  
PU Dökme Conta İzolasyonu  
Alüminyum Ekstrüzyon Mandallar  
Toz, Nem ve Suya Karşı  
Maksimum Dayanıklılık  
Çap 42 ve 60 mm Boruya Uygun  
Alüminyum Ekstrüzyon Kuyruk
- KULLANIM ALANLARI** : Caddeler, Otoyollar, Çevre Aydınlatmaları, Gezinti Yolları, Sokaklar, Her Tür Dış Mekan Aydınlatma Uygulamaları



AMS66 optional aluminium injection pole entrance (42 / 60 mm)  
Alüminyum enjeksiyon kuyruk opsiyoneldir (42 / 60 mm)

LAMP TYPE	A (mm)	B (mm)	H (mm)	K.G.	LUMEN
30W SMD Led	260	470	196	3,6	3.705
45W SMD Led	260	470	196	3,7	5.550
60W SMD Led	260	470	196	3,4	7.412

