





## GB 455-LD



- BODY** : Aluminium Extrusion Housing & Electrostatic Paint  
**GLASS/DIFFUSER** : P.C. Diffuser  
**REFLECTOR** : -  
**ELECTRICAL COMP** : Switch Mode, Constant Current LED Power Supply  
**PROTECTION CLASS**: IP 65  
**OTHER FEATURES** :  
**USAGE AREAS** : Parks, Walking Paths, Structure Surrounding Applications, Sites, Residential, Commercial Complexes, Applications where Decorative Outdoor Lighting Preferred

- GÖVDE** : Alüminyum Ekstrüzyon Gövde ve Elektrostatik Boyalı Gövde  
**CAM/DİFÜZÖR** : Polikarbon (P.C.) Difüzör  
**REFLEKTÖR** : -  
**ELEKTRİKSEL KOMP**: Switch Mode, Sabit Akım LED Güç Kaynağı  
**KORUMA SINIFI** : IP 65  
**DİĞER ÖZELLİKLER** :  
**KULLANIM ALANLARI** : Parklar, Yürüyüş Yolları, Bina çevreleri, Siteler, Konut Alanları-İş Merkezi Çevre Aydınlatmaları, Dekoratif Aydınlatmanın Tercih Edildiği Mekanlar



LAMP TYPE	SOCKET	A (mm)	B (mm)	H (mm)	K.G.
 30 W LED	-	150	750	4000	11,50
 40 W LED	-	150	750	4000	11,50
 50 W LED	-	150	750	4000	11,50
 55 W LED	-	150	750	4000	12,10
 60 W LED	-	150	750	4000	12,50

Flanş ölçüsü / Flange size: **220x220mm**

Profil Gövde ölçüsü / Profile Body : **150x80mm**

**BOX / KOLİ**  
(mm)

