


LAMP TYPE	A (mm)	B (mm)	H (mm)	K.G.
60W SMD Led	210	380	80	6,4
90W SMD Led	210	380	80	6,7
100W SMD Led	210	380	80	6,8
110W SMD Led	210	380	80	6,9
135W SMD Led	210	530	80	8,5
200W SMD Led	210	730	80	12,3
250W SMD Led	210	880	80	13,5
300W SMD Led	210	880	80	14,2
320W SMD Led	210	880	80	14,8

BOX / KOLI
(mm)



GPR-LD

- BODY** : Aluminium Extrusion Housing, Aluminium Injection Die-Cast Side Covers, Electrostatic Painted Side Covers
- GLASS/DIFFUSER** : Tempered Glass
- REFLECTOR** : -
- ELECTRICAL COMP** : Switch Mode, Constant Current LED Power Supply
- PROTECTION CLASS**: IP 66
- OTHER FEATURES** : High heat and shock resistancy
Optimum light distribution
Maximum resistancy to dust and water, Vertical 360°, Horizontal 180 degrees directional connectivity, Easy Accesable Electrical Components, Compartment intervene part of electrical components, Heat Melt Pu / Silicon Gashinging
- USAGE AREAS** : Sport Fields, Gymnasium areas, Building Facados, Marines, Ports, Tunnels, Crossroads, Aprons, Dams, Yards, Building Sites, Production Facilities

- GÖVDE** : Alüminyum Ekstrüzyon Gövde ve Elektrostatik Boyalı Gövde
Alüminyum, Elektrostatik Boyalı Yan kapaklar
- CAM/DİFÜZÖR** : Temperli Cam
- REFLEKTÖR** : -
- ELEKTRİKSEL KOMP**: Switch Mode, Sabit Akım LED Güç Kaynağı
- KORUMA SINIFI** : IP 66
- DiĞER ÖZELLİKLER** : Yüksek Isı ve Darbeye Dayanıklılık
Optimum Işık Dağılımı,
Toz ve Suya Karşı Maksimum Dayanıklılık,
Kolay Müdahale Edilebilir
Elektriksel Komponentler Kısmı,
Sıvı Dökme / Silikon Contalama,
Dikeyde 360°, Yatayda 180°
Derece Yönlendirilebilir Bağlantı.
- KULLANIM ALANLARI** : Spor Salonları, Bina Cepheleri, Limanlar, Şantiyeler, Barajlar, Kavşaklar, Tüneller, Apron Aydınlatması, İmalat Alanları



RGB Available On Request
RGB Uyarlanabilmektedir

